



ProSpec[®] - 2U6M2S Audio Mixer

FEATURE OVERVIEW:

- Live Performance contracting mixers designed to operate in Mono, Stereo, or LCR applications.
- 6 Channels of Burr-Brown Microphone Pre-Amplifiers and 2 stereo line input channels with selectable inputs..
- Balanced Left, Right, Center and Aux XLR outputs and dual Sum mono outputs use THAT Corporation Out-Smarts balanced output devices.
- Individual Solo and Channel On switches on each mono and stereo input channel.
- Each input channel is assignable to Left-Right OR Center mix bus.
- Mono input channels have High and Low Frequency EQ with variable (20Hz-200Hz) High Pass Filter.
- Stereo input channels have High and Low Frequency EQ with fixed High-Pass Filter
- Individual Left, Right, Center and Aux Output Metering with LIMITER active LED indicators.
- Mono input channel use Neutrik XLR/1/4" combo connectors and TRS insert and Direct Output connectors.
- Stereo input use individual 1/4" balanced left and right input connectors, RCA Inputs and (Stereo Input Channel 1) USB Digital or (Stereo Input Channel 2) front panel stereo input 1/8" connector.
- Low phase-shift, wide bandwidth electronic design derived from APB's Spectra and ProDesk products.
- Size: 3.5" Height -19" Width - 8.5" Depth.



All specifications and features are subject to change without notice